



Application

Accessories allowing to change the fan efficiency by reducing the voltage.

TLR 15 DS, TLR 25 DS – Single-phase (230V, 50Hz), continuously variable thyristor speed controller in surface-mounted version.

Technical data

- Power supply: 200-240V / 50 Hz
- Load Range:
 - 0,15 - 1,5A (TLR 15 DS)
 - 0,25 - 2,5A (TLR 25 DS)
- IP protection: IP 44
- Type of control: max - min
- Dimensions: 82x89x68 mm

Caution

Speed controllers can cooperate only with fans adapted to rotation speed control in one of the following ways.

All thyristor controllers can cause engine noise at low speeds - it is not recommended to lower the speed below 50% of the nominal value.

Nimityksiä

Tekniset tiedot

Modell	Märkspänning [V]	I max [A]	Temp. min. [°C]	Temp. max. [°C]
TLR 15 DS	230	1.5	0	40
TLR 25 DS	230	2.5	0	40

Dimensioner (mått i millimeter)

VENTUR tekniska ab, Göteborg

Manufakturvägen 7A
SE-417 07 Göteborg, Sweden

Tel. +46 31-23 50 80
fax +46 31-23 87 98

e-mail: info@ventur.se

VENTUR tekniska ab, Stockholm

Västberga Allé 1A
SE 126 30 HÄGERSTEN, Sweden

Tel. +46 8-534 101 90
fax +46 8-534 101 99

e-mail: info@ventur.se